

## Tender Specification

# SEEBURG A 1 Sub

12" double-band-pass sub-woofer with a usable range from 35 – 150 Hz and very high acoustic level of 132 dB. The shallow 30 cm depth of the enclosure enables installation in situations where very little space is available.

Eight M8 mounting points in the enclosure allow safe and simple horizontal or vertical mounting.

Compact dimensions at 35 x 80 x 30 cm (h x w x d) and low weight (17,5 kg)

The enclosure is constructed from 15 mm birch 11-ply, splash-proofed (IP44), Polyurea coated, RAL 9005 (other RAL colours available on special order).

### Product-Specifications:

|                                       |                                 |
|---------------------------------------|---------------------------------|
| <b>Speaker Components:</b>            | 1 x 12" Neodym, VC = 76 mm (3") |
| <b>Description:</b>                   | Passive Bass Extension          |
| <b>Power</b> (AES / Peak):            | 500 W / 1500 W                  |
| <b>Impedance</b> (nominal):           | 8 Ohm                           |
| <b>Maximum Level:</b>                 | 132 dB                          |
| <b>Usable Range:</b>                  | 35 Hz - 150 Hz (- 6 dB)         |
| <b>Connectors:</b>                    | 2 x Speakon NL4MP in/out        |
| <b>Rigging / Fittings:</b>            | 8 x M8                          |
| <b>Weight:</b>                        | 17,5 kg                         |
| <b>Size</b> (height x width x depth): | 35,0 x 80,0 x 30,0              |