

Tender Specification

SEEBURG GL 8 c / a

Passive extension module for SEEBURG GL systems to increase the vertical coverage angle and improve low-mid performance. With these modules, the GL 16 and GL 24 systems can be tailored to specific applications and demanding acoustic environments. GL 8 c / a modules are 2-way actively driven and can be directly connected to a GL 24 dp module.

Integrated steel-frame flying hardware allows combination with any other GL-series module.

Six M10 mounting points in the enclosure allow mounting of accessories.

The enclosure is plastic coated in RAL 9005 black (other RAL colours available on special order).

Simulation data sets are available for EASE, CATT and Ulysees.

Product-Specifications:

Speaker Components	2 x 6,5" Nd / 8 x 1" Nd Tweeter
Description	Cylindric Wave Radiator
Power (AES / Peak)	LF: 200 W / 600 W, HF: 75 W / 225 W
Impedance (nominal)	LF: 16 Ohm / HF: 16 Ohm
Maximum Level	121 dB
Usable Range (-6 dB)	80 Hz - 20 kHz
Coverage	100° horizontal, 31° vertical
Mechanical Splay Angle	24°
Connectors	2 x Speakon NL4MP in/out
Rigging / Fittings	6 x M10
Weight	8,5 kg
Size (height x width x depth)	38,0 x 18,9 x 25,8 (24,5) cm

Tender Specification

SEEBURG GL 8 i / a

Passive extension module for SEEBURG GL systems to increase the vertical coverage angle and improve low-mid performance. With these modules, the GL 16 and GL 24 systems can be tailored to specific applications and demanding acoustic environments. GL 8 i / a modules are 2-way actively driven and can be directly connected to a GL 24 dp module.

Integrated steel-frame flying hardware allows combination with any other GL-series module.

Eight M10 mounting points in the enclosure allow mounting of accessories.

The enclosure is plastic coated in RAL 9005 black (other RAL colours available on special order).

Simulation data sets are available for EASE, CATT and Ulysees.

Product-Specifications:

Speaker Components	2 x 6,5" Nd / 8 x 1" Nd Tweeter
Description	Cylindric Wave Radiator
Power (AES / Peak)	LF: 200 W / 600 W, HF: 75 W / 225 W
Impedance (nominal)	LF: 16 Ohm / HF: 16 Ohm
Maximum Level	121 dB
Usable Range (-6 dB)	80 Hz - 20 kHz
Coverage	100° horizontal, 7° vertikal
Mechanical Splay Angle	0°
Connectors	2 x Speakon NL4MP in/out
Rigging / Fittings	8 x M10
Weight	8,5 kg
Size (height x width x depth)	36,2 x 18,9 x 24,5 cm