

# Multifunctional Sound System - digitally powered **TSM 10 dp**



The TSM 10 dp is a multifunctional top class system in compact format with an integrated digital amplifier providing 500 / 150 Watt AES of power an DSP control. A range of factory-configured presets and volume settings can be selected. The TSM 10 dp is as equally well suited to use as a full range / HiMid loudspeaker as it is to monitor applications.

## PRODUCT SPECIFICATIONS

<b>Speaker Components</b>	10" Nd / 1"
<b>Description</b>	Multi Purpose Sound System
<b>Amp Power</b>	LF: 500 W AES / 110-230 V HF: 150 W AES / 110-230 V
<b>Rated Current</b>	0,5 A @ 230 V
<b>SPL</b> <small>Peak @ 1 m</small>	126 dB
<b>Max. Input Signal</b>	25 dBu
<b>DSP</b>	HDLM FPGA Processing 32 bit floating point
<b>AD / DA</b>	24 bit / 96 kHz
<b>Latency</b>	0,8 ms (analog in to analog out)
<b>Usable Range</b>	60 Hz - 19 kHz (-6 dB)
<b>Tuning Frequency</b> <small>excursion minimum</small>	68 Hz
<b>X - Overpoint</b> <small>acoustical</small>	Depends on preset
<b>Coverage</b> <small>horizontal / vertical</small>	90° x 60° - rotatable
<b>Max. Splay Angle</b>	- - -
<b>Connectors</b>	Neutrik XLR in/out Neutrik PowerCon in/out
<b>Handles</b>	1 x
<b>Rigging / Fittings</b>	3 x M10 / 6 x M8 35 mm pole mount
<b>Weight</b>	14,5 kg
<b>Size</b> <small>height x width x depth</small>	51,5 x 32,4 x 29,5 cm
<b>Order No.</b>	<b>00960/dp/II</b>



Ergonomically formed handle on the top surface.



Front grille version.



The TSM 10 dp features integrated digital amplifier electronics with a DSP controller. Various factory-configured presets and volume settings can be selected.

High-grade electronic components from the industrial sector and a first-class circuit design ensure excellent audio quality with low distortion and a minimal noise floor.

Highly efficient and "intelligent" limiter systems ensure optimum protection against overload, without restricting the possibilities offered by this high-performance sound system.

#### Level

Adjustment in 3 dB steps (-6 dB to +3 dB).

#### Status

##### Mute LED

Red light when the system is muted or under technically critical conditions.

##### Limit LED

Yellow light when the limiter is restricting the level.

##### Signal LED


Green light when the input signal exceeds -20 dBu.

##### Power LED

Green light when the system is switched on.

#### XLR

Symmetrical analog input max. Input +25 dBu. Effective filter protection against HF interference and DC Voltages. Electronically balanced to prevent noise.



#### Presets

##### Flat

This setting provides a linear frequency response with a neutral sound characteristics. Standard setting for many applications.

##### HP

Switches in a high pass filter for use in combination with a subwoofer.

##### Boost

Similar to the „Flat“ preset, but with increased low end response.

##### Soft

Reduces the level in the frequency range from 2.5 - 5 kHz, to which the ear is particularly sensitive. This setting is recommended for high level reproduction of highly compressed music tracks.

#### Mode - key

Switches between control modes: Status, Level and Presets.

#### Set - key

Setting of various values and Mute on / off.


#### PowerCon (blue)

Power supply  
~ 110-230 V / 16 A max.

#### PowerCon (grey)


~ 110-230 V / 16 A max.  
loop through connector.

## DIMENSIONS




## COVERAGE PATTERNS

2D Directivity Plot - horizontal



Presets - Frequency Response



### Flying Bracket



for TSM 10/ A 4 horizontal alignment,  
incl. screws  
(per unit: 2 pcs. adapters, M10 hex  
lock nuts, flat- and rubber washers)  
Order No. **01220/H/set**

### Flying Bracket



for TSM 10 / A 4  
incl. screws  
(per unit: 2 pcs. M10 x 20 ergostyle  
lobe knob and rubber washers)  
Order No. **01220/set**

### Ergostyle Lobe Knob



for flying brackets,  
M10 x 20, with grip, adjustable  
Order No. **08171**

### Rubber Washer



for flying brackets,  
40 mm  
Order No. **01205**

### Flange



35 mm Ø → M10,  
Order No. **08126**

### Flange



with ball and socket joint,  
with additional locking screw,  
M10 x 15, max. load 15 kg  
Order No. **08125**

### Truss Clamp



incl. M10 Adapter,  
max. load 15 kg  
Order No. **01221**

### Doughty Quick Trigger Clamp



max. load 250 kg  
Order No. **01223/250 kg**

### Ring Screw



M10– DIN 580  
Order No. **73700**

### TV Spigot



10 mm internal thread,  
28 mm Ø  
Order No. **08128**

### Steel Safety



4 mm x 600 mm, black,  
max. load 10 kg (BGI 810-3),  
quick connector undetachably  
Order No. **01376/4**

### Chain Fastener



VBS 7 mm  
Order No. **01378**

## ACCESSORIES TSM 10 dp

### Wall Mount



for U-brackets, max. load 40 kg,  
incl. screws  
(M10 x 70 mm socket head screw,  
M10 hex lock nut and flat washer)

for 8"-12" speakers  
Order No. **08130/F/269**

### Wall Mount



with tilt unit, max. load 40 kg  
Order No. **08130**

### Speaker Stand



K&M, incl. wind up,  
height 138,5 to 218 cm,  
max. load 50 kg,

Order No. **03011**

K&M, height 137,5 to 218,5 cm,  
max. load 50 kg,

Order No. **03010**

### Cover




for TSM 10 / A 4,  
padded  
Order No. **01242**

### Rain Cover



for TSM 10 / A 4  
Order No. **01242/outdoor**


### Honeycomb Grille



for TSM 10 front grille version,  
for replacement, foam behind

Order No. **97079/hex/compl.**


### Flight Case



for 2 pcs. TSM 10 / A 4,  
heavy duty, 9 mm birch multiplex,  
PVC coated, 2 x recessed sprung  
handles, 4 x butterfly catches,  
4 x 100 mm blue wheels, 2 pcs. with  
brake, interior lined with felt.

Order No. **16049**


### Flight Case Trunk



for 2 pcs. TSM 10 / A 4  
and accessories, heavy duty,  
9 mm birch multiplex, PVC coated,  
hinged lid, 6 x recessed sprung handles,  
2 x butterfly catches, 4 x 100 mm blue  
wheels, 2 pcs. with brake, interior lined  
with felt.

Order No. **16060**

### Flight Case Trunk



for 4 pcs. TSM 10 / A 4  
with flying brackets 01220,  
heavy duty, 9 mm birch multiplex,  
PVC coated, 6 x recessed sprung  
handles, 2 x butterfly catches,  
4 x 100 mm blue wheels, 2 pcs. with  
brake, interior lined with felt.

Order No. **16063**

### Hybrid Cable System



PowerCon-PowerCon / XLR-XLR

2,5 m Order No. **08462**

5 m Order No. **08464**

10 m Order No. **08466**

15 m Order No. **08468**

