

The G Sub 1801 is a universal 18" highpower subwoofer with truck-load compatible outside dimensions. The 58×75 cm footprint makes set-up with a loudspeaker pole mounted on the sub possible with even quite large mid-high systems. Mechanical and acoustic compatibility with the G Sub 1802 and Galeo C Sub allow a wide and versatile range of combination possibilities. This subwoofer combines very good handling with exceptional acoustic precision and depth of frequency.

PRODUCT SPECIFICATIONS


Speaker Components	18" Nd (4,5" VC)
Description	Passive Bass Extension
Power AES / Peak	1500 W / 4500 W
Impedance nominal	8 Ω
SPL 1 W / Peak @ 1 m	101 dB / 138 dB
Usable Range	30 Hz - 200 Hz (-6 dB)
Tuning Frequency excursion minimum	36 Hz
Connectors	3 x Speakon NL4 in/out Coding (2x): 1+/- loop thru, 2+/- Sub Coding (1x): 1+/- Sub, 2+/- loop thru
Handles	6 x
Rigging / Fittings	M20 on top Wheelboard fittings
Weight	45 kg (+ 8 kg wheelboard)
Size height x width x depth	58,0 x 58,0 x 78,0 cm
Order No.	00630



























2 x Galeo C + G Sub 1801

MEASUREMENTS

Frequency Response with Presets



Sensitivity 1 W @ 1 m + Impedance



ACCESSORIES G Sub 1801

5 2 5

Wheelboard

for G Sub 1801 / Galeo C Sub, also usable as Dolly, stackable, 8,0 kg Order No. **01268**

Dolly

for G Sub 1801 / Galeo C Sub, up to 3 units, 80 x 60 cm Order No. **01268/Dolly**

Twin Dolly

for up to 6 x G Sub 1801 / 3 x G Sub 1802 / 6 x Galeo C Sub, 118 x 60 cm Order No. **01273/Dolly**

Cover



for G Sub 1801 / Galeo C Sub by using wheelboard Order No. **01234/C**

Speaker Pole

250 mm, ø 35 mm, M20, with ring lock Order No. **03020**

Speaker Pole

M20, with crank Order No. **03023**





3