

Multifunctional premium-class compact 2-way system. The coaxial configuration in combination with a carefully designed large-area horn ensures absolutely constant response even off the main axis. High-power Neodym drivers and long-excursion coils provide high efficiency and reduced distortion. Four M10 threaded mounting points are available to mount accessories for installation or mobile applications.

# **PRODUCT SPECIFICATIONS**


Speaker Components	6,5" Nd (2" VC) / 1" Nd (1,7" VC)
Description	Multifunctional Coaxial Sound System
Power AES / Peak	200 W / 600 W
Impedance nominal	8 Ω
SPL 1 W / Peak @ 1 m	92 dB / 120 dB
Usable Range	80 Hz - 19 kHz (-6 dB)
Tuning Frequency excursion minimum	90 Hz
X - Overpoint acoustical	1,9 kHz
Coverage horizontal / vertical	90° x 60° - rotatable
Connectors	2 x Speakon NL4MP in/out Coding: 1 +/- HiMid, 2 +/- loop thru
Rigging / Fittings	4 x M10
Weight	5,5 kg
Size height x width x depth	31,0 x 20,0 x 22,0 cm
Order No.	01090






























https://www.seeburg.net/en/downloads

# **MEASUREMENTS**


# 2D Directivity Plot - horizontal




# Sensitivity 1 W @ 1 m + Impedance



# 2D Directivity Plot - vertical



# Frequency Response with Presets



## **ACCESSORIES X 1**



## Flying J-Bracket

for A 1 / GL 8 / X 1 / X 2 / TS Nano, horizontal and vertical alignment, incl. (white version: 1 x M10 x 20 socket head screws, black version: 1 x M10 x 20 adjustable handle screw)

Order No. 01200/set/w (RAL 9010) Order No. 01200/set





for flying brackets, adjustable M10 x 20

Order No. 08375/20

## Flange



with ball and socket joint, with additional locking screw, M10 x 15, max. load 15 kg

Order No. 08125

#### **Knurled Head Nut**



reduction screw for fastening M10 Pole Mount Adapter (08126)

Order No. **73755** 

# **Pole Mount Adapter**



35 mm ø -> M10 x 16 mm, M8 x 20 star knob screw Order No. 08126

35 mm ø -> M10 x 16 mm

Order No. 08126/II

#### **Wall Mount**



for permanent installation, incl. tilt angle stop, M10, max. load 15 kg

Order No. 08131/F/w (RAL 9010) Order No. 08131/F

## **Wall Mount**



ball and socket joint flange (08125) + 08125/plate Order No. 08125/set

## Quick Trigger Clamp - small



M10, max. load 20 kg Order No. 01223/20 kg

## **Truss Clamp**



incl. M10 Adapter, max. load 15 kg Order No. 01221

## **Ring Screw**



M10- DIN 580

Order No. 73700 (zinced) Order No. 73700/sw (black zinced)

# **Steel Safety**



4 mm x 600 mm, black, max. load 10 kg (BGI 810-3), quick connector undetachably

Order No. 01376/4

#### Bag



for 2 x A 1 / 2 x TS Nano / 2 x X 1, padded with pocket for accessories Order No. 01249









