



The G Sub 1501 dp is a particularly flat, self-powered high-performance 15" subwoofer. Four different presets and volume settings are available for adjustment to the application. With a base measurement of 60 x 60 cm it can also accommodate larger HiMid systems using speaker poles without toppling over. Due to its height of only 40 cm, it can easily be integrated in existing stage constructions. Easy handling, an exclusive and modern design and its deep bass reproduction make it a perfect choice for demanding applications.

PRODUCT SPECIFICATIONS

Speaker Components	1 x 15" ND - VC = 100 mm
Description	Digitally Powered Bass Extension
Power	1 x 1500 W EIAJ / 195-250 VAC
Max Line Input	+ 21 dBu
DSP	32 bit RISC
Internal Signal Path	32 bit fixed-point, 64 bit accumulator 64 bit IIR-coefficients
AD / DA	24 bit / 48 kHz
Latency	1.54 ms (analog in to analog out)
SPL max	131 dB
Frequency Range	35 Hz - 80 Hz / 120 Hz / 180 Hz
Tuning Frequency	Excursion minimum 42 Hz
Connectors	Neutrik XLR in/out Neutrik PowerCon in/out
Handles	2 x 2D
Fittings	M20 on top Wheelboard fittings
Weight	29,5 kg
Size	height x width x depth 40,0 x 60,0 x 60,0 cm
Order No.	00620/dp 1500



Robust honeycomb type speaker grille. Wheelboard fittings.




Fittings for wheelboard.




M20 flange on top.

DIMENSIONS




MEASUREMENTS

Presets - Frequency Response




Cardioid - Polar Diagram




APPLICATIONS




G Sub 1501 dp / GL 24



2 x G Sub 1501 dp / 2 x Galeo




4 x G Sub 1501 dp / K 24



2 x G Sub 1501 dp / G Sub 1501
Cardioid set-up.

The G Sub 1501 dp features integrated digital amplifier electronics with a DSP controller. Various factory-configured presets and volume settings can be selected.

High-grade electronic components from the industrial sector and a first-class circuit design ensure excellent audio quality with low distortion and effectively minimise static noise. Highly efficient and “intelligent” limiter systems ensure optimum protection against overload, without restricting the possibilities offered by this high-performance sound system.



ACCESSORIES G Sub 1501 dp

Speaker Pole

M20, adjustable, K&M
Order No. **03022**



Speaker Pole

M20, with crank, K&M
Order No. **03023**



Ceiling Mount

for Subwoofer
Order No. **08129**



Hybrid Cable System

PowerCon-PowerCon / XLR-XLR

2,5 m	Order No. 08462
5 m	Order No. 08464
10 m	Order No. 08466
15 m	Order No. 08468



Wheelboard

for G Sub 1501,
stackable
Order No. **01267**



Cover

for G Sub 1501
without wheelboard
Order No. **01239**



Cover

for G Sub 1501
by using wheelboard
Order No. **01239/WB**

