



Multifunctional high-end loudspeaker system with 12"/ 1.4" Nd drivers and a rotatable 90°x 60° horn. High output and speech intelligibility combined with low weight and compact size make it a very popular system. The TSM 12 is optimised for monitor applications, however it is equally suited to classic full range sound reinforcement applications, and can be mounted vertically or horizontally.

PRODUCT SPECIFICATIONS

Speaker Components	12" Nd / 1,4" Nd
Description	Multi Purpose Sound System
Power AES / Peak	600 W / 1800 W
Impedance nominal	8 Ω
SPL 1 W / Peak @ 1 m	98 dB / 131 dB
Usable Range	50 Hz - 19 kHz (-6 dB)
Tuning Frequency excursion minimum	54 Hz
X - Overpoint acoustical	850 Hz
Coverage horizontal / vertical	90° x 60° - rotatable
Max. Splay Angle	
Connectors	2 x Neutrik Speakon NL4MP in/out Coding: 1 +/- HiMid, 2 +/- loop thru
Handles	1 x
Rigging / Fittings	2 x M10 / 7 x M8 35 mm pole mount
Weight	20 kg
Size height x width x depth	60,6 x 36,0 x 33,7 cm
Order No.	00958




Connection Panel.



35 mm speaker stand flange.








Controller Setups:


https://www.seeburg.net/en/downloads

Sensitivity 1 W @ 1 m + Impedance 100 (NOT) 1

COVERAGE PATTERNS



2D Directivity Plot - vertical





Flying Bracket

for TSM 12 / A 6 incl. screws (per unit: 2 pcs. M10 x 30 adjustable handle screws) Order No. 01216/set



Flying Bracket

for TSM 12 / A 6, horizontal alignment, incl. screws (per unit: 2 pcs. adapters, M10 hex lock nuts, flat- and rubber washers)

Order No. 01216/H/set



Handle Screw

for flying brackets, adjustable M10 x 30

Order No. 08375/30



Ergostyle Lobe Knob

for flying brackets, M10 x 20, with grip, adjustable Order No. 08171



Rubber Washer

for flying brackets, 40 mm

Order No. **01205**



Flange

35 mm $\emptyset \rightarrow M10$,

Order No. 08126



max. load 250 kg

Order No. 01223/250 kg



Ring Screw

M10- DIN 580

Order No. **73700**



TV Spigot

10 mm internal thread,

28 mm Ø

Order No. 08128



Steel Safety

4 mm x 600 mm, black, max. load 10 kg (BGI 810-3), quick connector undetachably

Order No. 01376/4



Chain Fastener

VBS 7 mm

Order No. **01378**



ACCESSORIES TSM 12



Wall Mount

for U-brackets, max. load 40 kg, incl. screws (M10 x 70 mm socket head screw, M10 hex lock nut and flat washer)

for 8"-12" speakers Order No. 08130/F/269



with tilt unit, max. load 40 kg

Order No. 08130



Speaker Stand

K&M, incl. wind up, height 138,5 to 218 cm, max. load 50 kg,

Order No. **03011**



Honeycomb Grille

for TSM 12 front grille version, for replacement, foam behind

Order No. 97073/hex/compl.



Cover

for TSM 12 / A 6, padded

Order No. 01244



Rain Cover

for TSM 12 / A 6

Order No. 01244/outdoor



Flight Case

for 2 pcs. TSM 12 / A 6 heavy duty, 9 mm birch multiplex, PVC coated, 6 x recessed sprung handles, 4 x butterfly catches, 4 x 100 mm blue wheels, 2 pcs. with brake, partition walls, interior lined with felt.

Order No. **16010 P**







