

The TSM 15 dp is a multi-functional high-end loudspeaker system featuring integrated digital amplifier electronics with 1000 / 350 Watt AES powerand a DSP Controller. The 15" Neodym / 1.4" Neodym driver are each driven by a separate amplifier channel. A range of factory-configured presets and volume settings can be selected. It has been optimised for use as a monitor, however the rotatable horn makes the TSM 15 dp equally suited to classic fullrange sound reinforcement applications, either vertically or horizontally mounted. A wide range of possibilities for mounting flying accessories make the TSM 15 dp an interesting option for permanent installations.

PRODUCT SPECIFICATIONS

Speaker Components	15" Nd / 1,4" Nd
Description	Multi Purpose Sound System
Amp Power	LF: 1000 W AES / 110-230 V HF: 350 W AES / 110-230 V
Rated Current	0,95 A @ 230 V
SPL Peak @ 1 m	131 dB
Max. Input Signal	25 dBu
DSP	HDLM FPGA Processing 32 bit floating point
AD / DA	24 bit / 96 kHz
Latency	0,8 ms (analog in to analog out)
Usable Range	45 Hz - 18 kHz (-6 dB)
Tuning Frequency excursion minimum	50 Hz
X-Overpoint acoustical	Depends on preset
Coverage horizontal / vertical	90° x 60° - rotatable 60° x 50° - rotatable (optional)
Max. Splay Angle	
Connectors	Neutrik XLR in/out Neutrik PowerCon in/out
Handles	2 x
Rigging / Fittings	3 x M10 / 6 x M8 35 mm pole mount
Weight	27 kg
Size height x width x depth	69,8 x 45,0 x 41,0 cm
Order No.	00950/11/9060/dp (90° x 60°-version) 00950/11/6050/dp (60° x 50°-version)




The TSM 15 dp can be fitted with a narrower horn with a coverage angle of $60^{\circ} \times 50^{\circ}$.




The 35 mm threaded stand socket is integrated in the carrying handle.






COVERAGE PATTERNS




2D Directivity Plot - vertical





The TSM 15 dp features integrated digital amplifier electronics with a DSP controller. Various factoryconfigured presets and volume settings can be selected. High-grade electronic components from the industrial sector and a first-class circuit design ensure excellent audio quality with low distortion and a minimal noise floor. Highly efficient and "intelligent" limiter systems ensure optimum protection against overload, without restricting the possibilities offered by this high-performance sound system.



XLR

Symmetrical analog input, max. Input +25 dBu. Effective filter protection against HF interference and DC Voltages. Virtual ground lift.

<u>S E E B U R G</u>

acoustic line

3 TSM 15 dp

η



Flying Bracket for TSM 15 / A 8 / F 8

incl. screws (per unit: 2 pcs. M10 x 30 adjustable handle screws with axial bearing) Order No. **01217/set**

Flying Bracket for TSM 15 / A 8 horizontal alignment, incl. screws (per unit: 2 pcs. adapters, M10 hex lock nuts, flat- and rubber washers) Order No. 01217/H/set

Handle Screw

for flying brackets, axial bearing M10 x 30 Order No. **08374**

Ergostyle Lobe Knob for flying brackets, M10 x 20, with grip, adjustable Order No. 08171

Rubber Washer

for flying brackets, 40 mm Order No. **01205**



Flange 35 mm Ø –> M10,

Order No. 08126



Doughty Quick Trigger Clamp

max. load 250 kg Order No. **01223/250 kg**



Ring Screw M10– DIN 580 Order No. **73700**

TV Spigot 10 mm internal thread, 28 mm Ø Order No. 08128

Steel Safety

4 mm x 600 mm, black, max. load 10 kg (BGI 810-3), quick connector undetachably

Order No. 01376/4

Chain Fastener

VBS 7 mm Order No. **01378**



SEEBURG acoustic line



www.seeburg.com

ACCESSORIES TSM 15 dp



Wall Mount

for U-brackets, max. load 40 kg, incl. screws (M10 x 70 mm socket head screw, M10 hex lock nut and flat washer) for 15" speakers

Order No. 08130/F/400

Wall Mount

Speaker Stand

K&M, incl. wind up,

max. load 50 kg,

Order No. 03011

height 138,5 to 218 cm,

Honeycomb Grille for TSM 15 front grille version,

with tilt unit, max. load 40 kg Order No. 08130



Cover

for TSM 15 / A 8, padded Order No. 01240



Rain Cover

for TSM 15 / A 8,

Order No. 01240/outdoor

Flight Case

for 2 pcs. TSM 15 / A 8 / A 8 Sub, heavy duty, 9,0 mm birch multiplex, PVC coated, 6 x recessed sprung handles, 4 x butterfly catches, 4 x 100 mm blue wheels, 2 pcs. with brake, interior lined with felt.

Order No. 16012/pro









Hybrid Cable System

PowerCon-PowerCon / XLR-XLR 5 m Order No. 08464

10 m Order No. 08466 15 m Order No. 08468





5 TSM 15 dp

info@seeburg.net www.seeburg.com

