

Architectural Specifications

SEEBURG X 8

Multi-functional full-range system with 15" Nd low-mid and 1.4" Nd HF drivers. Optimised for use as a stage monitor, a side-fill or front-fill, or as a single system. The coaxial construction and large area 247x 195 mm rotatable horn ensure even response on or off axis. High-power neodymium magnets and long-excursion voice coils allow compact dimensions combined with high efficiency and reduced distortion.

The system is driven passively and can be used with a conventional amplifier.

Nine M10 mounting points are provided for easy and flexible installation with MultiRigg system and other mounting accessories. A 35 mm socket on the bottom surface allows mounting on a stand.

Cable connectors are recessed in a cut-out in the enclosure to allow unobtrusive cabling.

The enclosure is constructed from high-quality birch plywood, and RAL 9005 black plastic coated.

Custom colours are available.

Simulation data are available for Ease, Ulysses and CATT, and for the array-calculation software EASE Focus III.

Product Specifications:

Speaker Components	12" Nd (3,5" VC) / 1,4" Nd (3" VC)
Description	Multifunctional Coaxial Sound System
Power (AES / Peak)	500 W / 1500 W
Impedance (nominal)	8 Ohm
SPL (1 W / Peak @ 1 m)	99 dB / 131 dB
Usable Range	55 Hz – 18 kHz (- 6 dB)
Tuning Frequency (excursion minimum)	65 Hz
X - Overpoint (acoustical)	1 kHz
Coverage (horizontal / vertical)	80° / 60° (rotatable)
Connectors	2 x Speakon NL4MP in/out
Handles	2 x
Rigging / Fittings	9 x M10, to be used with MultiRigg™, 35 mm pole mount
Weight	18,5 kg
Size (height x width x depth)	50,0 x 36,0 x 33,0 cm

Architectural Specifications

SEEBURG X 8 dp

Multi-functional full-range system with 15" Nd low-mid and 1.4" Nd HF drivers. Optimised for use as a stage monitor, a side-fill or front-fill, or as a single system. The co-axial construction and large area 247x 195 mm rotatable horn ensure even response on or off axis. High-power neodymium magnets and long-excursion voice coils allow compact dimensions combined with high efficiency and reduced distortion.

The integrated digital amplifier electronics are based on high-efficiency Class D amplifier stages, coupled with low-noise FPGA DSP processing. Various default presets and volume settings are available for selection.

Electronic simulation of a transformer balanced input provides additional protection against disturbances caused by external interference. Remote monitoring and control is carried out via the Ethernet interface using SEEBURG Network Manager. Signal transmission (AoE) in accordance with the AES 67 standard is also possible.

Nine M10 mounting points are provided for easy and flexible installation with MultiRigg system and other mounting accessories. A 35 mm socket on the bottom surface allows mounting on a stand.

Cable connectors are recessed in a cut-out in the enclosure to allow unobtrusive cabling.

The enclosure is constructed from high-quality birch plywood, and RAL 9005 black plastic coated.

Custom colours are available.

Simulation data are available for Ease, Ulysses and CATT, and for the array-calculation software EASE Focus III.

Product Specifications:

Speaker Components	15" Nd (3,5" VC) / 1,4" Nd (3" VC)
Description	Multifunctional Coaxial Sound System
Amp Power (AES)	LF: 1500 W / HF: 400 W / 110-230 V
Rated Current	0,7 A
SPL (Peak @ 1 m)	134 dB
Max. Input Signal	25 dBu
DSP	DPLMx FPGA Processing 32 bit floating point
AD / DA	24 bit / 96 kHz
Latency	0,8 ms (analog in to analog out)
Usable Range	50 Hz - 18 kHz (- 6 dB)
Tuning Frequency (excursion minimum)	60 Hz
Coverage (horizontal / vertical)	80° / 60° (rotatable)
Connectors	XLR in, Ethercon, Powercon in
Handles	2 x
Rigging / Fittings	9 x M10, to be used with MultiRigg™, 35 mm pole mount
Weight	22,5 kg
Size (height x width x depth)	58,0 x 45,0 x 38,0 cm