

## Tender specification text

SEEBURG acoustic line

### TriSource 10

Microphone-compatible full-range loudspeaker in a very flat enclosure with long throw and good speech intelligibility even in large rooms. The special configuration of the two long-excursion 5" drivers and three horn loaded 1" tweeters is based on the 3-source principle. The result is particularly uniform vertical bundling to achieve higher direct-sound levels at longer distances. The mid-high section can be adjusted by +/- 10° to allow precise alignment without tilting the whole enclosure.

Custom finished covers are available to achieve a uniform visual impression in combination with video displays.

VESA norm mounting kit provides extensive options for mounting directly on VESA standard video displays. Wall mounting is also possible without any accessories.

The standard colour is RAL 9005 black. Other RAL colours available on request.

#### Product Specifications:

Speaker Components:	2 x 5" Nd (1,5" VC) / 3 x 1" Nd (1,1" VC)
Description:	Multi Media Column
Power (AES / Peak):	200 W / 600 W
Impedance (nominal):	4 Ohm
SPL (1W/Peak @ 1m)	90 dB/ 118 dB
Tuning Frequency:	55 Hz
Usable Range:	50 Hz - 20 kHz (- 6 dB)
X - Overpoint (acoustical):	1,2 kHz
Coverage (horizontal / vertical):	100° x 25° (nominal)
Connectors:	2 x Neutrik Speakon NL4MP in/out
Rigging / Fittings:	2 x M10, 14 x M5, 2 x fixing holes
Size (height x width x depth):	93,0 x 18,0 x 13,7 cm
Weight:	8,5 kg

Accessories and data sheets: [www.seeburg.com](http://www.seeburg.com)